Monitoring Changes in Land Cover with Remote Sensing: Some Relevant Concepts and Examples

Warren Cohen, Sean Healey, Robert Kennedy, Zhiqiang Yang*

USDA Forest Service & *Oregon State University, Corvallis, OR


Monitoring Changes in Land Cover with Remote Sensing: Some Relevant Concepts and Examples

- Matching needs with tools
- Data space and transformations
- Reference data and sampling
- A few examples from the North Coast and Cascades Network of NPS and environs


Two general approaches used in remote sensing:


Problem > tool Tool → problem

Landslide (NOCA-Flat Creek-7170,7169,7220,7276,7279)



500 m MODIS pixel







But, for monitoring, currently multi-temporal lidar is hard to come by

Bottom line...

- •Best tool not always available, but adequate tool may be
- Choose wisely




MODIS snow product



MODIS Tasseled Cap


Information in the Spectral Domain




n-space indices,e.g.,TasseledCap: b,g,w


If you have SWIR→
Exploit it!


With adequate tool and transformation, monitoring cover changes can be accomplished by monitoring changes in the data space...







Vector Image R: Rock G: Brdlf B: Yng Con. Vector Image R: Rock G: Brdlf B: Yng Con.











Red (date1) Green (date 2) Blue (date 3)












Percent Removal

0 100




Cover change 1996-1998


Basal area change 1996-1998

Validation from viewpoints (MORA,

Tasseled cap Landsat image IK




NOCA)
IKONOS color IR image



2004 oblique photo










Garmin GPS connected to PDA

Dell Axim 5 running ArcPad




Testing in white, training in black



Sampling to meet three competing goals:


- 1. SUFFICIENCY- Capture variability over landscape
- 2. EFFICIENCY- Minimize field travel costs
- 3. INDEPENDENCE- Avoid pseudoreplication


Assemble Spatial Data





Score Spectral Match

- Compare cumulative distribution of **sampled pixels** with that of **all pixels** within stratum
- Scale spectral match score (SMS) from 0 to 1









	Class 1	Class 2	Class 3
PC1	0.86	0.97	0.92
Greenness	0.92	0.98	0.94

Summary

- Parks need to monitor a variety of cover changes occurring over multiple scales
- Compromises are necessary as no single tool is suited to all problems and budgets are limited
- Important to be guided by the problem and find the tools needed, rather than force a given tool to solve problem it is not good at solving
- Transformations/indices of remote sensing data are numerous; if SWIR is available use it
- Monitoring changes in cover properties is accomplished by monitoring changes in original or transformed data space using any of a vast number of strategies
- Reference data are key to effective use of remote sensing and for characterizing uncertainty in remotely sensed products—for this a thoughtful sampling scheme may be advantageous